



Protect your values.

## PYRO-SAFE® CT Cable Tube

### Cable Tubes / Boxes

#### Description

Consisting of two half shells with intumescent inlay. Especially easy to use for the construction of simple penetration seals in core drillings.

#### Application Areas

- As individual penetration seals.
- As retrofitting devices.
- In plasterboard walls, solid walls, solid floors.



#### Delivery and Packaging

PYRO-SAFE® CT Cable Tube						
Packaging	Qty.		Qty.		Qty.	
Overall lengths	150 mm		200 mm		300 mm	
Dimensions	60	90	120	90	120	90 120
Package contents	2 half shells and 2 melamine resin stoppers					
Item number						
Ø 60	01276100		-		-	
Ø 90	01279100		01279200		01279300	
Ø 120	01281150		01281200		01281300	

All specifications in mm

Please contact us for further information:

✉ global@svt.de

Orders: order@svt.de

☎ +49 4105-40 90-0



Protect your values.

## PYRO-SAFE® CT Cable Tube

### Technical Data

Certificate of usability	ETA-16/0016
Coating	Grey, inner lining red
Material	<ul style="list-style-type: none"> <li>• PVC half shells,</li> <li>• Inner lining made of intumescent fabric,</li> <li>• Closure made of soft foam plugs</li> </ul>
Half shell closure	Click lock
Dimensions/ Variants	Ø 60 mm/Length 150 mm  Ø 90 mm/Length 150 mm Ø 90 mm/Length 200 mm Ø 90 mm/Length 300 mm  Ø 120 mm/Length 150 mm Ø 120 mm/Length 200 mm Ø 120 mm/Length 300 mm
Soundproofing	64 (-2;-6) dB Dn, e; Dn, w (C; Ctr)
Storage	Storage indoors at room temperature (+5 °C to +30 °C).
Safety information	No hazardous material according to German Hazardous Substances Act (GefStoffV) and no hazardous material according to German Act on the Transport of Dangerous Goods (GGVS/ADR).
Declaration of performance (DOP) no.	0128-PYRO-SAFE®-CT

### Applications

#### Penetration seal

	Certification	System name	Fire resistance class
CE	ETA-16/0016	PYRO-SAFE® CT	max. EI 120 acc. to EN 13501-2
		PYRO-SAFE® Novasit BM	
DIN	Z-19.53-2324	PYRO-SAFE® CT	Fire-resistant (90 min.)
	Z-19.53-2482	PYRO-SAFE® Novasit COMBI 90	
	Z-19.53-2329	PYRO-SAFE® Flammotect COMBI 90	
CLASSIFIED UL G US	C-AJ-1680, C-AJ-2833, F-A-3065, F-A-8054, W-J-3241, W-J-8077, W-L-3442, W-J-1314, W-L-1546	PYRO-SAFE® CT	FT-Rating max. 3 hrs. acc. to UL 1479

Errors, misprints and changes reserved. All of the information corresponds to the state of technology and the version of the standard that existed at the time of printing (12.2021).

We will gladly provide you with information on request regarding the legal and technical framework conditions or manufacturer specifications applicable to your individual case.

© Copyright svt Unternehmensgruppe, Seevetal. PYRO-SAFE® is a registered trademark ® of the svt group, Seevetal.